

e-STUDIO™ 5506AC

e-STUDIO™ 6506AC

e-STUDIO™ 7506AC

- > Color Multifunction Printer
- > Up to 75 PPM
- > Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



INNOVATIVE FEATURES, VERSATILE CONNECTIVITY.

The Toshiba e-STUDIO7506AC series helps workgroups connect, integrate and simplify while improving efficiency, productivity and the professionalism of presentations.

Higher Robust Speeds include 55/65/75 brilliant color pages per minute and 65/75/85 monochrome pages per minute, respectively.

Fast Dual-Scan Document Feeder handles up to 300 sheets at a time and seamlessly scans both sides of each page in a single pass to produce a full 240 images per minute (IPM).

Fast First Copy Out Times include 6.4/6.4/5.4 seconds for full-color printing and 5.2/4.5/4.1 seconds (respectively) for black and white printing.

9" Tablet-Style Touch Screen works intuitively, helping you access instructions, functions, and commands with the swipe of the finger.

Banner Printing produces impressive signage as large as 12" x 47" using our unique AquaAce media.

Print Around eliminates printing bottlenecks by allowing other print jobs to go around one job that's held-up due to requiring a specific paper size, type or, in some cases, color toner.

Limitless Job Reservation will queue up multiple copy or print jobs so users can send jobs whenever.

Saddle/Fold Capabilities offer saddle-stitch finishing and the ability to fold without stapling.

Scan-to and Print-from USB lets you print straight from your USB drive or scan documents to it.

Advanced e-BRIDGE Next Technology enables the MFP to drive Toshiba's internally developed embedded solutions or those from a third party with ease.

Notifications Feature takes the hassle out of checking for depleted supplies or maintenance needs.

Paper Volume Indicators on the front panel make it easy to see the paper sizes, types and levels in each cassette.

Help Button provides instant, thorough explanations straight from the manual to help as needed.



TOSHIBA INNOVATION AT ITS FINEST.

When it comes to seamless workflow and simplified integration, the e-STUDIO7506AC series represents the finest Toshiba has to offer. The latest e-BRIDGE Next technology enables complete third-party integration and support for internally driven solutions. A universal driver along with PCL 6, PS3, and XPS support provide fast and easy connectivity to Windows®, Macintosh® and more.

AirPrint and Mopria™ support means mobile users can print to the MFP with ease. The e-BRIDGE Print & Capture application provides additional capabilities including the ability to scan from the MFP back to your mobile device. Also, a Dual-Line Fax option can handle heavy fax volumes with ease.

Cloud Support

New Scan-to-Cloud and Cloud Print capabilities increase productivity by allowing users to access, store and print documents remotely from the MFP. Whether it's Dropbox, OneDrive or Google Drive, the new e-STUDIO7506AC series makes scanning to these cloud-based locations a breeze, while embedded support for Google Cloud Print enables easy printing to the MFP from anywhere you may be.

Advanced Security

Even more important than functionality is the security offered by the e-STUDIO7506AC series. Such technological advancements include:

- > A 320GB Self-Encrypting Drive (SED) with Automatic Drive Invalidation (ADI) & Data Overwrite capability provides top level security
- > FIPS 140-2 Validated SED meets and exceeds government requirements
- > IPsec is available to securely encrypt data sent to and from the MFP

Environmental Responsibility

Because we have been working to protect the environment as well as your security, you can rest assured Toshiba has what it takes to protect both.

- > RoHS compliance, the use of recycled plastics, and Low-Power (0.6W) Super Sleep Mode work to help the environment
- > EPEAT Gold Registered in the global registry for greener electronics, designed to help purchasers choose products that reduce environmental impact
- > Energy Star V2.0 meets the latest, more stringent requirements



IMPRESSIVE EVEN BEFORE YOU TURN IT ON.

1 Accessory Tray & Keyboard Options

- GR1250 – Accessory Tray
- GR9000 – Bluetooth Keyboard
- GR1260 – 10-Key Numeric Keypad

2 Finishing Options

- MJ1111 – 50-Sheet Console Finisher
- MJ1112 – 50-Sheet Saddle Stitch Finisher
- MJ6106 – Hole Punch Unit
- KA6551 – Side Exit Tray

3 Connectivity Options

- GD1370 – Fax Unit/2nd Line for Fax Unit
- GN4020 – Wireless LAN/Bluetooth Module

4 Additional Paper Options

- MP2502 – 2,500 Sheet Large Capacity Feeder

Additional Option Highlights

- > IPsec Security Enabler
- > Multi-Station Print Enabler
- > Embedded OCR Enabler



Toshiba's e-STUDIO7506AC series offers the best of the best, enabling large workgroups to improve productivity and connectivity while simplifying the overall workflow.

Double the Scan Speed

A 300-sheet high-speed, high-capacity Dual-Scan Document Feeder (DSDF) produces up to 120 IPM simplex and 240 IPM duplex.

Bluetooth/WiFi Option

Bluetooth feature provides support for a wireless keyboard to simplify workflow processes at the MFP, while the WiFi capability enables WiFi-Direct printing making it ideal for mobile users

Volumes and Volumes

A high monthly copy volume is 480K/540K/600K respectively. Impressive toner yields are 39,200 color and 106,600 black and white (each at 5%).

Multi-Station Print Enabler

Toshiba's internally developed Multi-Station Print Enabler allows users to send print jobs from their desktop and retrieve them at any available MFP by simply swiping their badge and authenticating at that device.

Advanced e-BRIDGE Next Technology

Built on Linux[®], this latest generation e-BRIDGE Next architecture features an Embedded Web Browser, an Intel Atom™ dual-core processor, 4GB RAM and a 320GB FIPS 140-2 Validated SED enabling the MFP to easily drive Toshiba's internally developed solutions or even third-party applications.

e-STUDIO™ 5506AC/6506AC/7506AC

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
Display	9" Color WVGA Touch Screen Tiling Display
Copy Speed	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
First Copy Out	Color: 6.4/6.4/5.4, Monochrome: 5.2/4.5/4.1
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
Multiple Copying	Up to 9,999 Copies
Paper Capacity	4-Drawer: 2,280 Sheets/Max. 4,780 Sheets Tandem Drawer: Standard 3,520 Sheets/Max. 6,020 Sheets Standard 300-Sheet DSDF
Original Feed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Index, Duplex: 9.3-110 lb Index
Scan Speed & Weights	LD
Max. Original Size	Drawers: 540 Sheets-ST-R to 12" x 18"
Paper Feed Sizes	Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner 2,500-Sheet Ext. LCF LT-Only 4-Drawer: Standard 540 Sheets x 4-16 lb Bond-140 lb Index Tandem LCF 1,160 Sheets x 2-16 lb Bond-140 lb Index Plus 540 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 120 Sheets-16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-140 lb Index Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Paper Weights	
Duplex	
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 480K/540K/600K Month (Color: 100%)
Weight	Approx. 47.0 lb
Approx. Dimensions	37.6" (W) x 28.9" (D) x 48.3" (H)
Toner Yield	CMY: 39,200, K: 106,600 @ 5%
Power Source	120 Volts, 50/60 Hz, 16 Amps
Power Consumption	Maximum 2.0kW (120V)
CPU	Intel Atom™ 1.75 GHz (Dual-Core)
Memory	4GB
Hard Disk Drive	320GB Self-Encrypting Drive FIPS 140-2 Validated

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
Print Resolution	600 x 600 dpi @ 5 bit, 1,200 x 1,200 dpi (Color/2 bit) or 3,600 x 1,200 dpi (BW/with Smoothing) PS3 Only
Operating Systems	Windows® Vista, Windows Server® 2008/R2, Windows® 7, 8, 8.1, 10, Windows Server® 2012/R2, Macintosh® (Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11), Unix®, Linux®
Network Protocols	TCRIP (IPv4, IPv6), NetBIOS over TCRIP, IPX/SPX® for Novell® Environments, EtherTalk® for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.1.1) w/Authentication, AppleTalk PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows® Vista SP2 (32-bit, 64-bit), Windows Server® 2008 SP2 (32-bit, 64-bit), Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8/8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows® 10 (32-bit, 64-bit), Mac OS® X 10.6.8, 10.7.4, 10.8, 10.9, 10.10, 10.11
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (high-speed) Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint™, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
Device Management	TopAccess, EFMS 6.2 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC 15408 EAL3+), IEEE2600.1, IEEE802.1X, Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp
*Compliant with IEEE2600.1 in High Security Mode.

Environmental Stds. Certification

Energy Star (V2.0), EPEAT Gold, RoHS
WHQL (Windows 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell, Citrix, SAP

Scan Specifications

Scan Speed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Sim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Additional Paper Options	MP2502	Embedded OCR Enabler Single License Five Licenses	GS1080 GS1085
Finishing Options	MJ1111 MJ1112 MJ6106 KA6551 KN1103	Multi-Station Print Enabler Single License Five Licenses Advanced Scanning (ReFile) SharePoint Connector Exchange Connector Google Drive Connector	GS1090 GS1095 GB1280V8 GB1440 GB1450 GB1540
Connectivity/Security Options	GD1370 GN4020 GP1190A GR9000 GR1250 GR1260 GR1290 GS1010 GP1080 GS1007	FAX Unit/2nd Line for FAX Unit Wireless LAN/Bluetooth Hardcopy Security Printing Bluetooth Keyboard Accessory Tray Panel 10-Key Option Card Reader Holder Meta Scan Enabler IPsec Enabler Unicode Font Enabler	Miscellaneous Options Accessible Arm Harness Kit for Coin Controller KJ2560 GQ1280



www.edgetechuganda.com
info@edgetechuganda.com
Plot 69 kyaddondo 1 rd Namirembe

Tel:
+256 776 250 883
+256 702 250 883
+256 312 244 300
+256 200 300 700